

Model: SHX-D4040 Aluminum Casting Thick Box



SHX - D4040 is a pneumatic shielding box, it has larger working size. Suitable for testing wireless network card, cordless phones and some bigger wireless communication equipment. The shielding box casted by aluminum alloy material, good shielding, and structure is firm. Its use electrical control operation, simple and effort. In addition, can according to customer needs, configure the I/O data interface. The shielding factor as high as 80 dB, frequency up to 6 GHz. The product has been successfully won recognition at home and abroad customers, and get the high praise.

Product Features:


- ◆ Aluminum alloy material and solid design
- ◆ Using the latest shielding materials, absorbing strong, high blocking
- ◆ Complete test interface design, let you more convenient with tester
- ◆ Using extrusion type sealing design, get a better shielding effect
- ◆ Large internal space, make more product testing

Product Application:

SHX - D4040 shielding box is suitable for wireless communications test, EMI test, coupling, RF function test, etc.

For small communication products, such as the development of GSM, CDMA, 3G mobile phones, cordless phones, Bluetooth production and maintenance

SHX-D4040 Specifications	
Frequency Range(GHz)	0.8~6GHz
Isolation	≥80 dB @2.4GHz
	≥70 dB @5.8GHz
RF Interface	SMA*4
DC Power Supply	DC*1
Data Interface	USB*2
	RS-232*1
	RJ45*1
AC Power Supply	AC 110V-220V/50-60HZ
Working Size (mm)	400 (W)*400 (D)*240 (H)
Dimensions (mm)	426 (W)*426 (D)*316 (H)
Housing	Aluminum
Weight(kg)	30KG
Operating Temperature(°C)	0-50
Colour	Brown(Customer select available)



Opt1626

PCIE/MINIPCIE滤波器



Opt1563

AC



Opt1667

RS232*1+USB*2+RJ45*1+DC*1



Opt1613

RS232*1+USB*2+RJ45*2



Opt1614

VGA*1+USB*2+RJ45*2



Opt1681

DC*2+USB*2+RJ45*2

◆ 可按您的要求定做各种规格屏蔽箱或滤波器

Notes:

1. Dimensions Tolerance $\pm 2\%$
2. Custom designs available.

Model: SHX-D3020 Straight On And Down Box



SHX-D3020 shielding box adopts advanced casting process, filter and automatic control technology, the design fully conform to the requirements of the production, lab test. Verification By the department of national metrology, The shielding effectiveness of similar products in the country in a leading position. Widely used in GSM, GPS, PHS, BLUETOOTH, WLAN testing, etc.

SPECIFICATIONS:

SHX-D3020 Specifications	
Frequency Range(GHz)	0.8~3GHZ
Isolation	≥65 dB
RF Interface	N(f) outside and 2SMA(f) inside*2
DC Power Supply	DC*1
Data Interface	DB9(p) outside and DB9(s) inside 100PF
	DB25(p) outside and DB25(s) inside 1000PF
AC Power Supply	AC 110V-220V/50-60HZ
Working Size (mm)	280 (W)*175(D)*120(H)
Dimensions (mm)	350 (W)*272(D)*284(H)
Housing	Aluminum
Weight(kg)	19KG
Operating Temperature(°C)	0-50
Colour	Brown(Customer select available)

Notes:

1. Dimensions Tolerance ±2%
2. Custom designs available.

Model: SHX-D4560 Drawer Type Shield Box



SHX-D4560 shielding box adopts advanced casting process, filter and automatic control technology, the design fully conform to the requirements of the production, lab test. Verification By the department of national metrology, The shielding effectiveness of similar products in the country in a leading position. Widely used in GSM, GPS, PHS, BLUETOOTH, WLAN testing, etc.

SPECIFICATIONS:

SHX-D4560 Specifications	
Frequency Range(GHz)	0.8~6GHZ
Isolation	≥70 dB @2.4GHz
	≥65 dB @5.8GHz
RF Interface	SMA*4
DC Power Supply	DC*1
Data Interface	USB*2
	DB15*1
	RJ45*1
AC Power Supply	AC 110V-220V/50-60HZ
Working Size (mm)	330*130*150(Fixture size)
Dimensions (mm)	525 (W) *435 (D) *675 (H)
Housing	Aluminum
Weight(kg)	68KG
Operating Temperature(°C)	0-50
Colour	Brown(Customer select available)

Special features: the clamp hand safety features

Notes:

1. Dimensions Tolerance ±2%
2. Custom designs available.

Model: SHX-SD4345 Pneumatic Shield Box



SHX-D4345 shielding box adopts advanced casting process, filter and automatic control technology, the design fully conform to the requirements of the production, lab test. Verification By the department of national metrology, The shielding effectiveness of similar products in the country in a leading position. Widely used in GSM, GPS, PHS, BLUETOOTH, WLAN testing, etc.

SPECIFICATIONS:

SHX-SD4345 Specifications	
Frequency Range(GHz)	0.8~6GHZ
Isolation	≥75 dB @2.4GHz
	≥70 dB @5.8GHz
RF Interface	SMA*10
DC Power Supply	DC*1
Data Interface	USB*2
	RS-232*1
	RJ45*1
AC Power Supply	AC 110V-220V/50-60HZ
Working Size (mm)	450 (W)*430 (D)*300 (H)
Dimensions (mm)	460 (W)*440 (D)*382 (H)
Housing	Cold-rolled steel, surface baking varnish
Weight(kg)	25KG
Operating Temperature(°C)	0-50
Colour	Maize(Customer select available)

Notes:

1. Dimensions Tolerance ±2%
2. Custom designs available.

Model: SHX- MD3020 Shield Box



SHX-MD3020 shielding box adopts advanced casting process, filter and automatic control technology, the design fully conform to the requirements of the production, lab test. Verification By the department of national metrology. The shielding effectiveness of similar products in the country in a leading position. Widely used in GSM, GPS, PHS, BLUETOOTH, WLAN testing, etc.

SPECIFICATIONS:

SHX-MD3020 Specifications	
Frequency Range(GHz)	0.8~2.5GHz
Isolation	≥70 dB
RF Interface	N-SMA*2
DC Power Supply	DC*1
Data Interface	DB9(p) outside and DB9(s) inside 100PF
	DB25(p) outside and DB25(s) inside 1000PF
AC Power Supply	AC 110V-220V/50-60HZ
Working Size (mm)	200 (W)*220 (D)*160 (H)
Dimensions (mm)	470 (W)*330 (D)*230 (H)
Housing	Aluminum, surface baking varnish
Weight(kg)	15KG
Operating Temperature(°C)	0-50
Colour	Brown(Customer select available)

Notes: Customer select filter available

Notes:

1. Dimensions Tolerance ±2%
2. Custom designs available.

Model: SHX-MS4040-G Manual Signal Shield Box



SHX-MS4040-G shielding box adopts advanced casting process, filter and automatic control technology, the design fully conform to the requirements of the production, lab test. Verification By the department of national metrology. The shielding effectiveness of similar products in the country in a leading position. Widely used in GSM, GPS, PHS, BLUETOOTH, WLAN testing, etc.

SPECIFICATIONS:

SHX-MS4040-G Specifications	
Frequency Range(GHz)	0.8~6GHZ
Isolation	≥70 dB @2.4GHz
	≥65 dB @5.8GHz
RF Interface	SMA*4
DC Power Supply	DC*1
Data Interface	USB*2
	RS-232*1
	RJ45*1
Working Size (mm)	400 (W)*400 (D)*400 (H)
Dimensions (mm)	450 (W)*530 (D)*435 (H)
Housing	Cold-rolled steel, surface baking varnish
Weight(kg)	30KG
Operating Temperature(°C)	0-50
Colour	Maize(Customer select available)

Notes:

1. Dimensions Tolerance ±2%
2. Custom designs available.

Model: SHX-MD3080 Shield Box



SHX-MD3080 shielding box adopts advanced casting process, filter and automatic control technology, the design fully conform to the requirements of the production, lab test. Verification By the department of national metrology, The shielding effectiveness of similar products in the country in a leading position. Widely used in GSM, GPS, PHS, BLUETOOTH, WLAN testing, etc.

SPECIFICATIONS:

SHX-MD3080 Specifications	
Frequency Range(GHz)	0.8~3.0GHz
Isolation	≥65 dB
RF Interface	SMA-SMA*2
Date Interface	USB*1
Working Size (mm)	144 (D)*94 (W)*35 (H)
Dimensions (mm)	165 (D)*100 (W)*63.5 (H)
Housing	Sheet metal(stainless steel)
Weight(kg)	2.5KG
Operating Temperature(°C)	0-50
Colour	Grey white(Customer select available)

Notes:

1. Dimensions Tolerance ±2%
2. Custom designs available.

Model: SHX-MD3090 Shield Box



SHX-MD3090 shielding box adopts advanced casting process, filter and automatic control technology, the design fully conform to the requirements of the production, lab test. Verification By the department of national metrology, The shielding effectiveness of similar products in the country in a leading position. Widely used in GSM, GPS, PHS, BLUETOOTH, WLAN testing, etc.

SPECIFICATIONS:

SHX-MD3090 Specifications	
Frequency Range(GHz)	0.8~3.0GHz
Isolation	≥65 dB
RF Interface	SMA-SMA*2
Date Interface	USB*1
Working Size (mm)	175 (D) *90 (W) *35 (H)
Dimensions (mm)	180 (D) *110 (W) *56 (H)
Housing	Sheet metal (stainless steel)
Weight(kg)	2.5KG
Operating Temperature(°C)	0-50
Colour	Grey white (Customer select available)

Notes:

1. Dimensions Tolerance ±2%
2. Custom designs available.