

型号 16 路高频功分器



型号	工作频段 (GHz)	驻波比	插入损耗 Max.(dB)	幅度平衡 Max.(dB)	相位平衡 Max.(Deg.)	平均功率 (W)	隔离度 Min.(dB)	连接器形式	外形尺寸 LxWxH(mm)
SHX216-060180	6-18	≤1.6	≤3.5	≤±0.6	±8°	20	≥18	SMA(F)	210x44.5x12.7
SHX216-060265	6-26.5	≤1.7	≤4.0	≤±0.7	±8°	20	≥16	SMA(F)	210x44.5x12.7
SHX216-060400	6-40	≤1.8	≤5.1	≤±0.8	±9°	20	≥16	2.92(F)	210x44.5x12.7
SHX216-100265	10-26.5	≤1.7	≤4.0	≤±0.6	±6°	20	≥17	SMA(F)	210x44.5x12.7
SHX216-100400	10-40	≤1.8	≤4.9	≤±0.6	±8°	20	≥17	2.92(F)	210x44.5x12.7
SHX216-180265	18-26.5	≤1.6	≤3.6	≤±0.5	±6°	20	≥18	SMA(F)	210x36x12.7
SHX216-180400	18-40	≤1.8	≤5.0	≤±0.6	±7°	20	≥17	2.92(F)	210x36x12.7

标称阻抗：50Ω

备注：

1. 所有外形尺寸单位 mm, 尺寸公差±5%